



49" Video Wall Display

This product features ultra narrow bezel, LG commercial grade IPS panel and patented tile technology. It supports USB port and internet content publishing. Smart functions include scheduled power on/off, intelligent temperature control, brightness adjustment and etc.



Easy Setup with RS232 In And Out

Each video wall display features and RS232 in and out connection. RS232 is a standard of serial communication between a PC and multiple displays, and makes video wall configuration a breeze.



Full HD 1080p with HDMI

- Scale up or scale down. Endless possibilities with a multiple display control.
- Automatic power on/off function allows you to schedule when the display will turn on or off. Schedule by time of day or calendar date.
- Abundant I/O ports: Video, Audio, VGA, DVI, RGB/HV, YPbPr, HDMI, USB, RS232, RJ45

Model	PD49NL
Display Screen Size	48.5"
Resolution	1920 x 1080
Product Size (inches)	42.42"[H] x 23.93"[W] x 4.48"[D]
Display Size (inches)	42.28"[H] x 23.79"[W]
Net Weight	57.32 lbs.
Brightness	450 cd/m ²
Aspect Ratio	16:9
Contrast Ratio	1300:1 (Typ.)
Input Power Voltage	AC 100-240 V (50Hz-60Hz)
Working Temperature	32° to 122° F
Colors	10Bit[D], 1.06 Billion
Video Format	avi, mp4, ts, trp, mkv, mov, mpg, dat, vob
Audio Format	mp3, wma, m4a, aac
Picture and Text	bmp, jpg, jpeg, png, txt
Content Input Method	USB, LAN, WAN
Ports	Video, VGA, DBI, REG/HV, HDMI, YPbPr, Audio, RS232, RJ45
Power Consumption	160W
Viewing Angle	178°
Time Control	Supports multi on and off task, automatically switch channel
Accessories	Manual, Guarantee Card, Remote Control, Power Cable, VGA Cable, RS232 Cable, RJ45 Cable, DID Silica Gel Gasket
VESA Pattern	300 x 600mm